

# ST. CROIX PELLET INSERT AND STOVE SPECIFICATIONS

ELEMENT-P



ECLIPSE-P



ASHBY-P



PRESCOTT EXL



PRESCOTT EXP



HASTINGS



|                                   | ELEMENT-P           | ECLIPSE-P           | ASHBY-P                     | PRESCOTT EXL        | PRESCOTT EXP        | HASTINGS            |
|-----------------------------------|---------------------|---------------------|-----------------------------|---------------------|---------------------|---------------------|
| Width                             | 20 3/8"             | 25"                 | 45"<br>(with std. surround) | 24 3/4"             | 24 3/4"             | 25"                 |
| Height                            | 30 5/8"             | 35 5/8"             | 32"<br>(with surround)      | 31 3/4"             | 34"                 | 32 1/2"             |
| Depth                             | 20"                 | 21 5/8"             | 24"                         | 26"                 | 26"                 | 23 1/2"             |
| Vent Size                         | 3" rear vent        | 4" rear vent        | 3" rear vent                | 3" rear vent        | 3" rear vent        | 3" rear vent        |
| Minimum Fireplace Opening (W)     | —                   | —                   | 24"                         | —                   | —                   | —                   |
| Minimum Fireplace Opening (H)     | —                   | —                   | 20 3/4"                     | —                   | —                   | —                   |
| Minimum Fireplace Opening (D)     | —                   | —                   | 16"                         | —                   | —                   | —                   |
| Heating Capacity <sup>1</sup>     | Up to 1,800 sq. ft. | Up to 2,100 sq. ft. | Up to 1,800 sq. ft.         | Up to 1,800 sq. ft. | Up to 1,800 sq. ft. | Up to 1,800 sq. ft. |
| Hopper Capacity <sup>2</sup>      | 45 lbs.             | 85 lbs.             | 60 lbs.                     | 75 lbs.             | 75 lbs.             | 40 lbs.             |
| Burn Rate <sup>3</sup> (lbs./hr.) | On/Off-4.5          | On/Off-6.3          | On/Off-4.5                  | On/Off-4.5          | On/Off-4.5          | On/Off-4.5          |
| Emission Rate (g./hr.)            | .660                | 1.562               | .981                        | .532                | .532                | 1.215               |
| BTUH <sup>3</sup>                 | Up to 40,000        | Up to 54,500        | Up to 40,000                | Up to 40,000        | Up to 40,000        | Up to 40,000        |
| Ash Drawer                        | Yes                 | Yes                 | Yes                         | Yes                 | Yes                 | Yes                 |
| Electronic Ignition               | Yes                 | Yes                 | Yes                         | Yes                 | Yes                 | Yes                 |
| Digital Controls                  | Yes                 | Yes                 | Yes                         | Yes                 | Yes                 | Yes                 |
| Room Thermostat                   | Yes                 | Yes                 | Yes                         | Yes                 | Yes                 | Yes                 |
| Shipping Weight                   | 255 lbs.            | 400 lbs.            | 267 lbs.                    | 285 lbs.            | 299 lbs.            | 427 lbs.            |

<sup>1</sup>Heating capacity will vary with home construction and climate.

<sup>2</sup>Hopper capacities will vary depending on the weight and volume of the fuel.

<sup>3</sup>Burn rate and BTUH will vary with fuel.

Products, specifications and prices subject to change without notice. Consult our Owner's Manuals for all final dimensions. St. Croix products are manufactured in the U.S.A.

Certified to: ASTM E2779-2010 to 2020 phase, less than 2 g/hr

ASTM E1509-04 / U.L. 1482/U.L.C. S627

Oregon Administrative Rules: 814-23-900 thru 814-23-909

Power requirements: 120 Volts AC (Ignition: 400-500 watts,

Steady State: 200-250 watts)

